


**LS1808 Surge & Safety X2Y3, SMD LS1812**

Kapazitätswerte & Max Spannung							
Wert (pF)	Code	Volt max	Dielectric	Wert (pF)	Code	Volt max	Dielectric
<b>LS1808 Serie</b>				<b>LS1808 Serie</b>			
5.0	5R0	250Vac/3KV	NPO (COG)	470	471	250Vac/3KV	NPO (COG)
6.8	6R8	I	NPO (COG)	560	561	I	NPO (COG)
8.2	8R0	I	NPO (COG)	680	681	I	NPO (COG)
10	100	I	NPO (COG)	820	821	I	NPO (COG)
12	120	I	NPO (COG)	1000	102	▼	NPO (COG)
15	150	I	NPO (COG)				
18	180	I	NPO (COG)				
22	220	I	NPO (COG)				
27	270	I	NPO (COG)	<b>LS1812 Serie</b>			
33	330	I	NPO (COG)	1000	102	250Vac/3KV	NPO (COG)
47	470	I	NPO (COG)	1200	122	I	NPO (COG)
56	560	I	NPO (COG)	1500	152	I	NPO (COG)
68	680	I	NPO (COG)	2200	222	▼	NPO (COG)
100	101	I	NPO (COG)				
120	121	I	NPO (COG)				
150	151	I	NPO (COG)				
180	181	I	NPO (COG)				
220	221	I	NPO (COG)	EN60950, EN132400, IEC60384-14			
270	271	I	NPO (COG)				
330	331	I	NPO (COG)				
390	391	▼	NPO (COG)				

Irrtümer, Änderungen vorbehalten

<b>1808</b>	<b>N</b>	<b>471</b>	<b>K</b>	<b>302</b>	<b>N</b>	<b>(X) T</b>	<b>M</b>
Bauform	Dielectric	Kapazität	Toleranz	Spannung	Kontaktierung	Gurtung	Marking
LS1808 LS1812	N = NPO (COG)	100 = 10pF 101 = 100pF 471 = 470pF 102 = 1000pF	J = 5% K = 5%	302 = 3000V	N = Ni RoHS	T = gegurtet X = Dicke	Marking

Aktuelle Preise auf Anfrage / Current Prices on Request